



DURO DYNE CANADA INC. 5030 FRANÇOIS CUSSON, LACHINE, QUEBEC H8T 1B3
TEL: (514) 422-9760 FAX: (514)-636-0328
www.durodynecanada.ca

*VOC/LEED Sealer & Adhesive Summary

Product Code	DWN	WB-S2	WSA	WIT	S-2	IA-94
VOC grams/litre (less water)	28 g/l	48 g/l	<30 g/l	<5 g/l	539 g/l	513.1 g/l
Solids %	69%	69%	57%	55%	45%	27.1%
Weight-lb./gl.	11.7 lbs/US gl.	11.7 lbs/US gl.	11.8 lbs/imp. gl.	11.8 lbs/imp. gl.	8.9 lbs/US gl.	6.3 lbs/US gl.

VOC information on GN & GU Gasketing products:

VOC: Since VOC ratings apply to wet adhesives that evaporate as part of the application process, the solvent is removed from the adhesive on the gasket when fabricated. The GN and GU gasketing is thus a dry product for which VOC are not required.

MSDS: Duro Dyne is complying fully with the Federal Occupational Safety and Health Administration (OSHA) standard 29 C.F.R. 1910.1200. The GN and GU do not require an MSDS because it is considered an "Article" and articles are exempt from the MSDS provisions.

***VOC:** Volatile Organic Compounds

LEED: Leadership in Energy and Environmental Design

(Re IA-94) March 25, 2011